

REF · WEB231

Anti Ox

Anti Ox - Antioxidant Agent



DESCRIPTION

Anti Ox is an antirust agent that protects against moisture and corrosion and prevents the deterioration of metal surfaces. Leaves a thin, permanent protective layer that does not dry. It replaces the protective baths of chrome, wax, lacquer, paint, acrylics, etc. Easy application and removal, which results in a reduction of costs. Anti Ox is useful in the industry in general, shipping industry, mechanical workshops, construction etc.

DOSAGE AND USE INSTRUCTIONS

Shake and spray abundantly on the surfaces to be protected.

TECHNICAL DATA

Appearance	Aerosol.
Density (20°C)	0.95 +/- 0.02 g/ml.

MAIN COMPONENTS

Oils, antirust agents.

PRESENTATION

12x400 ml.

USE OR HANDLING PRECAUTIONS

DANGER UN No.: UN1950



DO NOT SWALLOW.

H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501b	Dispose of contents/container to hazardous or special waste collection point.
	Do not mix with other chemicals.

Consult the Safety Data Sheet (SDS) before using the product.

MANUFACTURER

Detervic S.A.

Polígon Industrial Can Malloles · Sant Llorenç Desmunts, 32
08500 Vic · Barcelona

ES · CA · EN · FR · PT

DOCUMENT CONTROL

Rev. 1
Issued: 28/02/2018
Page 1 / 1

SALES CONTACT

T. +34 938 891 344
info@instaquim.com
instaquim.com