

REF · WEB232

Di elec

Dielectric degreaser - slow evaporation



DESCRIPTION

Di elec is a dielectric degreaser of slow but total evaporation and high cleaning power. It does not leave no film or any residue. Di elec is suitable for cleaning of generators, alternators, motors, transformers, electrical distribution panels and mechanical elements. Does not damage metal surfaces. It can lightly attack some kind of plastics, especially polystyrene.

DOSAGE AND USE INSTRUCTIONS

Spray at a distance of aprox. 30 cm, use a dry brush if necessary. Let it work and dry with an air jet afterwards, if it is possible. Do not use while the system is working. It can lightly attack some kind of plastics, especially polystyrene.

TECHNICAL DATA

Appearance	Aerosol.
Density (20°C)	1.21 +/- 0.02 g/ml.

MAIN COMPONENTS

Contains tetrachlorethylene, aliphatic C9-C11 hydrocarbons (aromatics <2%).

PRESENTATION

12x400 ml.

USE OR HANDLING PRECAUTIONS

DANGER UN No.: UN1950



DO NOT SWALLOW.

H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H351	Suspected of causing cancer.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251	Do not pierce or burn, even after use.
P264a	Wash the hands thoroughly after handling.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.

MANUFACTURER

Detervic S.A.

Polígon Industrial Can Malloles · Sant Llorenç Desmunts, 32
08500 Vic · Barcelona

ES · CA · EN · FR · PT

DOCUMENT CONTROL

Page 1 / 2

SALES CONTACT

T. +34 938 891 344

info@instaquim.com

instaquim.com

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501b	Dispose of contents/container to hazardous or special waste collection point. Do not mix with other chemicals.

Consult the Safety Data Sheet (SDS) before using the product.

MANUFACTURER

Detervic S.A.

Polígon Industrial Can Malloles · Sant Llorenç Desmunts, 32
08500 Vic · Barcelona

ES · CA · EN · FR · PT

DOCUMENT CONTROL

Page 2 / 2

SALES CONTACT

T. +34 938 891 344

info@instaquim.com

instaquim.com