

REF · WEB178

Instaflok

Coagulant flocculant for swimming pools



DESCRIPTION

Product suitable for eliminating particles in suspension and improving the filtration system. Mixable in water in all proportions. It is not necessary to change the pH of the water to obtain an excellent result. Do not use with diatomaceous filters.

DOSAGE AND USE INSTRUCTIONS

Maintenance: 5 ml per 1000 l of water. Recovery treatment: 20 ml per 1000 l of water. INSTAFLOK should be added on the skimmers maintaining a high water flow rate.

TECHNICAL DATA

Appearance Transparent liquid.

pH 3.0 +/- 0.5

Density (20°C) 1.15 +/- 0.05 g/ml

MAIN COMPONENTS

Contains aluminium poly(hydroxichloridesulphate).

PRESENTATION

25 kg.

USE OR HANDLING PRECAUTIONS

DANGER UN No.: UN3264



DO NOT SWALLOW

H290 May be corrosive to metals.

H318 Causes serious eye damage.

P102 Keep out of reach of children.

P234 Keep only in original container.

P280C Wear protective gloves, clothing and eye protection.

P305+P351+P338-P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

P406 Store in a corrosion resistant container with a resistant inner liner.

P390 Absorb spillage to prevent material damage.

Do not mix with other chemicals.

Consult the Safety Data Sheet (SDS) before using the product.

MANUFACTURER

Detervic S.A.

Polígon Industrial Can Malloles · Sant Llorenç Desmunts, 32
08500 Vic · Barcelona

ES · CA · EN · FR · PT

DOCUMENT CONTROL

Rev. 13

Issued: 20/05/2024

Page 1 / 1

SALES CONTACT

T. +34 938 891 344

info@instaquim.com

instaquim.com