

REF · WEB330

Lubri al

Anti-seize grease - aluminium



DESCRIPTION

Lubri al is a lubricant with aluminium microparticles and corrosion inhibitors. It forms a lubricating film that prevents metal-metal contact and therefore wear. It prevents seizures due to high pressures and high temperatures and resists water and steam. Working temperature from -20°C to 1000°C. Lubri al is useful in the assembly of chain pins, articulations, hinges, threaded unions in general, adjustment of valves, taps, keys, as a lubricant of bearings, etc.

DOSAGE AND USE INSTRUCTIONS

Pre-clean the parts where the product will be applied. Shake and spray on the area to be lubricated.

TECHNICAL DATA

Appearance	Aerosol.
Density (20°C)	0.65 +/- 0.05 g/ml.

MAIN COMPONENTS

Contains aliphatic C6 hydrocarbons (n-hexane <5%).

PRESENTATION

12x400 ml.

USE OR HANDLING PRECAUTIONS

DANGER UN No.: UN1950



	DO NOT SWALLOW.
H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251	Do not pierce or burn, even after use.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501b	Dispose of contents/container to hazardous or special waste collection point.
	Do not mix with other chemicals.

Consult the Safety Data Sheet (SDS) before using the product.

MANUFACTURER

Detervic S.A.

Polígon Industrial Can Malloles · Sant Llorenç Desmunt, 32
08500 Vic · Barcelona

ES · CA · EN · FR · PT

DOCUMENT CONTROL

Page 1 / 1

SALES CONTACT

T. +34 938 891 344

info@instaquim.com

instaquim.com